

11-20-00



Assistant Commissioner for Patents
Washington, DC 20231
ATTN: BOX UTILITY APPLICATION

UTILITY
PATENT APPLICATION
TRANSMITTAL
Docket No.: 99-478
Date: November 21, 2000



Sheet 1 of 2

U.S. Express Mail Label No.: EL661474258US

Inventor Name(s):
THOMAS P. MULLER

Title:
APPARATUS AND METHOD OF PROVIDING A WORK MACHINE

- ☒ Fee Transmittal Form Attached in Duplicate
- ☒ Specification and Claim(s) [Total Pages
- ☒ Drawing(s) [Total Sheets

Declaration [Total Pages

- ☒ Newly Executed (Original or Copy)
- ☐ Copy From Prior Application (37 CFR § 1.63(d))
- ☐ Deletion of Inventor(s) (37 CFR § 1.63(d)(2))
(Signed Statement Attached)
- ☒ Assignment Papers (Cover Sheet and Document(s))
- ☐ 37 CFR § 3.73(b) Statement (if applicable) ☐ Power of Attorney
- ☐ English Translation Document (if applicable)
- ☐ Information Disclosure Statement (IDS)/PTO-1449
- ☐ Copies of IDS Citations
- ☐ Preliminary Amendment
- ☒ Return Receipt Postcard (Specifically Itemized)
- ☐ Certified Copy of Priority Document(s)
- ☐ Other

--Continue Next Page--

If a Continuing Application

☐ Continuation ☐ Divisional ☐ Continuation-In-Part (CIP)

of prior Application No.: ;

Examiner : ; and

Group/Art Unit: .

☐ Cancel Claims:

For Continuations or Divisional Applications only: The entire disclosure of the prior application, from which an oath or declaration is supplied, as set forth above, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference.

Correspondence Address:

☒ Customer Number or Bar Code Label:

or

☐ Correspondence address below:

Name:

Address:

City:

State:

Zip Code:

Country:

Attorney/Agent: Byron G. Buck III

Registration No.: 40,537

Signature: 

Date: 11/21/00

Caterpillar Inc.

FEE TRANSMITTAL

for FY 2000

Patent fees are subject to annual revision.
 Small Entity payments must be supported by a small entity statement,
 otherwise large entity fees must be paid. See Forms PTO/SB/09-12,
 See 37 C.F.R. §§ 1.27 and 1.28.

TOTAL AMOUNT OF PAYMENT (\$) 2,280

Complete if Known

Application Number (Unassigned)
 Filing Date (Herewith)
 First Named Inventor THOMAS P. MULLER
 Examiner Name (Unassigned)
 Group / Art Unit (Unassigned)
 Attorney Docket No. 99-478

METHOD OF PAYMENT (check one)

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:

Deposit Account Number 03-1129

Deposit Account Name

☒ Charge Any Additional Fee Required Under 37 CFR §§ 1.16 and 1.17

2. ☐ Payment Enclosed:

☐ Check ☐ Money Order ☐ Other

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity	Small Entity	Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
105	130	205	65			Surcharge - late filing fee or oath	
127	50	227	25			Surcharge - late provisional filing fee or cover sheet	
139	130	139	130			Non-English specification	
147	2,520	147	2,520			For filing a request for reexamination	
112	920*	112	920*			Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*			Requesting publication of SIR after Examiner action	
115	110	215	55			Extension for reply within first month	
116	380	216	190			Extension for reply within second month	
117	870	217	435			Extension for reply within third month	
118	1,360	218	680			Extension for reply within fourth month	
128	1,850	228	925			Extension for reply within fifth month	
119	300	219	150			Notice of Appeal	
120	300	220	150			Filing a brief in support of an appeal	
121	260	221	130			Request for oral hearing	
138	1,510	138	1,510			Petition to institute a public use proceeding	
140	110	240	55			Petition to revive - unavoidable	
141	1,210	241	605			Petition to revive - unintentional	
142	1,210	242	605			Utility issue fee (or reissue)	
143	430	243	215			Design issue fee	
144	580	244	290			Plant issue fee	
122	130	122	130			Petitions to the Commissioner	
123	50	123	50			Petitions related to provisional applications	
126	240	126	240			Submission of Information Disclosure Stmt	
581	40	581	40			Recording each patent assignment per property (times number of properties)	
146	690	246	345			Filing a submission after final rejection (37 CFR § 1.129(a))	
149	690	249	345			For each additional invention to be examined (37 CFR § 1.129(b))	
Other fee (specify) _____							
Other fee (specify) _____							

SUBTOTAL (1) (\$) 710

2. EXTRA CLAIM FEES

Large Entity	Small Entity	Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
101	680	201	345			Utility filing fee	710
106	310	206	155			Design filing fee	
107	460	207	240			Plant filing fee	
108	690	208	345			Reissue filing fee	
114	150	214	75			Provisional filing fee	

SUBTOTAL (2) (\$) 1,570

Large Entity	Small Entity	Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
103	18	203	9			Claims in excess of 20	
102	78	202	39			Independent claims in excess of 3	
104	260	204	130			Multiple dependent claim, if not paid	
109	78	209	39			** Reissue independent claims over original patent	
110	18	210	9			** Reissue claims in excess of 20 and over original patent	

SUBTOTAL (3) (\$) 0

SUBMITTED BY

Name (Print/Type) Byron G. Buck II

Signature

Registration No. (Attorney/Agent)

40,537

Complete if applicable

Telephone (309) 675-6717

Date 11/21/2000

WARNING:

Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Description

APPARATUS AND METHOD OF PROVIDING A WORK MACHINE

5 This application claims the benefit of prior
provisional patent application Serial No. 60/210,058.

Technical Field

10 This invention relates generally to an
apparatus and method of providing at least one work
machine and, more particularly, to determining the
productivity of a work machine.

Background Art

15 Work machines having an attached implement,
such as motorgraders, excavators, mining shovels,
backhoe loaders, track-type tractors, wheeled
tractors, compactors, wheel loaders, and the like, are
used for moving earth. Such implements may include
20 blades, impact rock rippers, buckets, and other
material handling apparatus. Typically, work machines
may be configured to perform various work cycles. For
example, a wheel loader typically has a bucket used to
rack, lift, dump, and lower a load and may be used to
25 carry a load from one point to another point. These
capabilities of a wheel loader are typically combined
to perform a work cycle such as a hard bank loading,
load and carry, truck loading cycle and the like.

30 In general, a work machine has a certain
productivity, in terms of tons of material handled per

09717573-112100

gallon of fuel consumed. Productivity of the work machine is of imperative importance to the customer because it is generally directly related to the income and/or revenues received by the customer. Therefore, customers desire a work machine provider to execute a guaranteed productivity customer support agreement (CSA). These CSAs contractually guarantee a predetermined productivity of the work machine to the customer, thereby effectively shifting the risk of nonperformance (breakdown) to another party like the work machine provider or manufacturer.

Ideally, work machine providers, whether they be manufacturers, dealers, rental fleet operators or the like, could monitor the work machine and determine when maintenance and service of the work machine was necessary prior to a significant deterioration of productivity, or even worse a breakdown of the work machine, thereby enabling providers to execute a CSA. However, to date, work machine providers have had difficulty accurately and consistently determining the need for maintenance and service of a work machine before productivity significantly deteriorates. Customer support agreements typically available today are generally based on a level of machine maintenance or machine availability.

Accordingly, the art has sought an apparatus and method of determining the productivity of a work machine which: senses the work performed by the machine; calculates the productivity of the machine;

selects a guaranteed productivity customer support agreement in response to the productivity; may be used in a timely and efficient manner; and is more economical to manufacture and use.

5 It is known from United States Patent number 5,065,349 to Thomas of November 12, 1991, to measure the performance of an individual who rents a vehicle or other complex machine to be sure the machine is not abused during such rental use. Further, it is known
10 from United States Patent number 5,631,832 to Hagenbuch of May 20, 1997, to process data derived from the weight of a load carried by a hauling vehicle, detect the change in the weight of the load, formulate data indicative of hauling conditions of the
15 vehicle, and accumulate historical data for formulating management decisions directed to the future operation of the vehicle. Additionally, it is known from United States Patent number 5,808,907 to Shetty et al. of September 15, 1998, to provide
20 information relating to a machine to a user by sensing predetermined events relating to the machine, producing corresponding event signals, delivering the event signals to a remote site, comparing the event signals to a profile of events corresponding to the
25 user and delivering a notification signal to the user if the event signals match a profile.

 However, it is currently difficult for a work machine provider to accurately and consistently predict when a work machine needs service and
30 maintenance prior to productivity significantly

09717573-1-100

deteriorating so that the provider can economically execute a guaranteed productivity customer support agreement with a customer.

The present invention is directed to
5 overcoming one or more of the problems as set forth above.

Disclosure of the Invention

09747573-112100
10 In an embodiment of the present invention a system for determining a guaranteed productivity support agreement for a customer is provided. The system includes at least one machine sensor and at least one computer. The at least one machine sensor is adapted to provide at least one machine sensor
15 signal indicative of the work performed by the machine. The computer is adapted to receive the sensor signal, calculate the productivity of the machine and select a guaranteed productivity customer support agreement in response to the productivity.

20 In an embodiment of the present invention a method for determining a guaranteed customer support agreement for customer is provided. The method includes the steps of determining the productivity of the machine and generating a guaranteed productivity
25 customer support agreement establishing at least one minimum productivity limit.

In an embodiment of the present invention a system for measuring operator productivity of at least one work machine for customer is provided. The system
30 includes at least one machine sensor and a computer.

0971573-112100

The machine sensor is adapted to provide at least one machine sensor signal indicative of the operation performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine. The computer includes a central processing unit and is adapted to receive the sensor signals and calculate the productivity of the machine, the productivity being a function of an amount of fuel consumed and at least one of a payload handled by the machine and an operation performed by the machine.

In an embodiment of the present invention a method of providing incentives to an operator of a work machine is provided. The method includes the steps of determining a work cycle performed by the machine, determining the productivity of the machine, comparing the productivity of the machine with normalized operator productivity data for the work cycle, determining a skill level of the operator in response to comparing the productivity of the machine with the productivity data, determining the change in skill level of the operator in response to comparing the productivity of the machine with the productivity data and providing an incentive to the operator for at least achieving a predetermined change in skill level.

In an embodiment of the present invention a system for determining when a work machine needs service is provided. The system includes at least one machine sensor and a computer. The at least one machine sensor is adapted to provide at least one machine sensor signal indicative of the operation

performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine. The computer is adapted to receive the sensor signals, calculate the productivity of the machine, determine the skill level of the operator, calculate the change in productivity of the machine and skill level of the operator, determine whether the productivity of the machine is deteriorating and provide a service notice signal in response to determining whether the productivity of the machine is deteriorating.

In an embodiment of the present invention, a work machine adapted to be controlled by an operator and for acting upon a load through a plurality of work cycles is provided. The work machine includes a frame, plurality of ground engaging devices, an operator compartment, an implement, an engine and a system. The plurality of ground engaging devices support the frame. The operator compartment is supported by the ground engaging devices. The implement has a linkage for operably connecting the implement to the frame. The engine is operably coupled to the ground engaging devices. The system includes at least one machine sensor and a computer. The at least one machine sensor is adapted to provide at least one machine sensor signal indicative of the operation performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine. The computer is adapted to receive the sensor signals, calculate the productivity of the

machine and determine a skill level of an operator of the machine.

In an embodiment of the present invention a system for determining fees to be paid by a customer that are based on machine productivity is provided. The system includes at least one machine sensor and a computer. The at least one machine sensor is adapted to provide at least one machine sensor signal indicative of the operation performed by the machine, the payload handled by the machine, and the amount of fuel consumed by the machine. The computer is adapted to received the sensor signals, calculate the productivity of the machine and determine a skill level of the operator of the machine.

Brief Description of the Drawings

For a better understanding of the invention, reference may be made to the accompanying drawings in which:

Fig. 1 is a side view of a work machine of a preferred embodiment of the present invention;

Fig. 2 is a graph of normalized operator productivity data for an embodiment of the present invention;

Fig. 3 is a graph of productivity versus fuel consumed for several work cycles for an embodiment of the present invention;

Fig. 4 is a flow chart of software logic implemented in an embodiment of the present invention.

Best Mode for Carrying Out the Invention

09717573.112100

A preferred embodiment of the present invention provides an apparatus and method of providing at least one work machine to a customer. The following description uses a wheel loader as an example only. This invention can be applied to other types of work machines and other types of implements as is well known in the art. Other examples include, mining shovels, motorgraders, backhoe loaders, track-type tractors, wheeled tractors, compactors, track-type rotors, and the like.

In Fig. 1, a work machine 100 having a frame 105, plurality of ground engaging devices 110, an operator compartment 115 an implement 120, an engine 125 and a system 130.

The plurality of ground engaging devices 110 support the frame 105 and the operator compartment 115. The implement 120 may have a linkage 135 for operably connecting the implement 120 to the frame 105. The engine 125 is operably coupled to the ground engaging devices 110.

The system 130 includes at least one machine sensor (not shown), a computer 140, preferably associated with at least one data storage device 145, and preferably includes a communication device 150.

The machine sensor is adapted to provide machine sensor signals indicative of the work performed by the work machine 100. Preferably, the

09717573-41200

machine sensors include at least one operation sensor adapted to provide operating sensor signals indicative of the operation performed by the machine, at least one payload sensor adapted to provide payload sensor signals indicative of the payload handled by the machine and at least one fuel sensor adapted to provide fuel consumption sensor signals indicative of the amount of fuel consumed by the machine. The operation sensor may be any or a combination of pressure sensors or transducers, flow sensors or transducers, radial or axial sensors, transducers or potentiometers, sonic, microwave, laser, waveguide or other device or system for determining the angles of displacement about a pivot joint or relationship of the implement 120 to the rest of the work machine 100 or for determining the movement of the ground engaging devices 110 with respect to the rest of the work machine 100. Similarly, the payload sensor could be any or a combination of pressure sensors or transducers, flow sensors or transducers, radial or axial sensors, transducers or potentiometers and other sonic, microwave, laser, waveguide or other device or system for indicating the weight of the payload handled by the work machine 100.

As should be appreciated, the at least one fuel sensor may be any or a combination of a fuel tank fuel level sensor; a fuel or lubricating or hydraulic fluid line pressure or flow sensor or transducer; a device for measuring, controlling and/or accumulating fuel injection to a combustion chamber of engine 125;

a suction gas monitoring system; an exhaust gas monitoring system; and the like.

5 The at least one data storage device 145 may be any of a number of data storage devices adapted to store information on a storage medium such as random access memory, read-only memory, electrically erasable programmable read-only memory, traditional hard drives, optical discs and the like. Preferably, the data storage device 145 stores information including
10 empirical data, values representing a message record, values representing the sensor signals, normalized operator productivity data for at least one work cycle, normalized expected improvement in skill level data for at least one work cycle and guaranteed
15 productivity customer support agreements.

09712573-112100

The computer 140 is adapted to receive these sensor signals and calculate the productivity of the machine 100. The computer 140 preferably includes a central processing unit for receiving the sensor
20 signals and calculating the productivity of the machine 100. Preferably, computer 140 is one of many readily available computers capable of processing numerous instructions. It should be appreciated that computer 140 may include multiple processing units
25 configured in a distributed structure environment and forming a system. Such distributed processors may be continuously or intermittently connected through any of numerous communications devices including such devices as direct hardwired data links, radio and

other transmission devices, optical transmission devices and the like.

Preferably, the productivity is a function of the amount of fuel consumed and at least one of the
5 payload handled by the machine and the operation performed by the machine. However, it should be appreciated that the productivity could be determined by other methods of calculating or approximating the work performed by the machine 100 within a time
10 period.

In one or more embodiments of the present invention it may be advantageous for the computer 140 to be adapted to perform one or more of the tasks explained below.

15 Advantageously, the computer 140 compares the sensor signals to empirical data and determines a work cycle performed by the machine 100. It is appreciated that the specific values of the empirical data depend upon the specific model and in many cases
20 configuration of the work machine 100. However, such data can be readily and easily determined through experimentation by monitoring the movements of the machine and the operating characteristics of the control systems, including flows, pressures and the
25 like such that particular characteristics of the machine 100 can be identified and associated various work cycles.

Advantageously, computer 140 may provide a productivity notice signal indicative of the
30 productivity of the machine 100.

A CSA could be any of a number of documents containing terms of sale, rental, lease, and the like and includes terms guaranteeing the level of productivity of machine 100. Computer 140 preferably
5 selects a CSA with a minimum productivity limit substantially corresponding to the productivity of the machine 100 during the trial period. The productivity limit may vary during the term of the CSA with the experience of the operator.

10 Preferably the computer 140 continues to monitor the machine 100 and continuously calculates the productivity of the machine 100 and determines the skill level of the operator. Additionally, it is advantageous for the computer 140 to calculate the
15 change in productivity of the machine and skill level of the operator over a predefined time period. It should be appreciated that numerous different time periods could be readily and easily used without deviating from the scope of the present invention as
20 defined in the appended claims. For example, many different time periods could be used depending upon the resolution desired. Preferably, this could be calculated on a daily basis.

Advantageously, the data storage device is
25 adapted to store the change in productivity of the machine and skill level of the operator. This historical data may be provided to the computer and/or operator, service organization, customer or owner of the machine 100.

0972573-112100

Preferably, computer 140 determines whether the productivity is deteriorating. Advantageously, the computer 140 compares the change in productivity of the machine 100 with the normalized expected improvement in skill level data to determine whether the productivity is deteriorating.

For example, in Fig.3 load and carry data curve 300, hard bank data curve 305 and clean up data curve 310 all are representative curves indicating an expected relationship between the tons of payload handled, vertical axis 330, and the fuel consumed by a machine 100, horizontal axis 335. As the skill level of the operator increases with experience the tons of payload handled by the machine 100 increases with the fuel consumed. Truck loading data curve 315 is representative of a relationship between the tons of payload handled and the fuel consumed by machine 100 and indicates a potential problem. Productivity of machine 100 generally corresponding to these data curves may advantageously be compared with the normalized expected improvement in skill level data to determine if the productivity has changed as the skill level of the operator is generally expected to increase as a result of additional experience. If the skill level of the operator is expected to increase as shown in Fig. 2, then computer 140 would determine that there was a deterioration in productivity of the machine 100 if the change in productivity of machine 100 changes from initial productivity 320 to subsequent productivity 325 during a truck loading

work cycle. It should be understood that tolerances of a reasonable amount may be employed in the comparisons. The actual tolerance employed is dependent, at least partially, on the resolution desired and can be readily and easily determined through numerical analysis or experimentation for the particular model and configuration of the machine 100.

If computer 140 determines there was a deterioration in productivity of the machine 100, then it is advantageous for the computer 140 to provide one or more notice signals indicating any of a variety of levels of deterioration in productivity. Such notice signals may include a productivity deterioration warning notice signal, a service notice signal, a CSA warning notice signal and the like. A productivity deterioration warning notice signal would preferably provide an early warning and indicate that the productivity is beginning to deteriorate. A service notice signal would preferably indicate that the productivity has deteriorated and that maintenance should be performed. A CSA warning notice signal would preferably provide a warning and indicate that the productivity is deteriorating and is falling or will likely fall below the minimum productivity limit guaranteed in the CSA.

Preferably, computer 140 generates at least one message record. The message record advantageously includes at least one of the sensor signals and notice signals.

Referring back to Fig. 1, communication device 150 is preferably adapted to receive the message record and provide the message record to at least one of the operator, a service organization, the customer and an owner of the machine. The communication device 150 is generally a device capable of transferring the message record and may include such devices as data transmission wires, modems, radios and other signal transmission devices, optical transmission devices, wave guides, microwave communication devices, satellite communication devices and the like. Communication device 150 advantageously includes a user interface system that may be any or a combination of interface devices readily available such as radio reception and generation devices, scanners, modems, printers, fax machines, bar code readers, touch screens, and preferably a video display or graphic display in combination with a keyboard. Additionally, it may be advantageous for the interface system to include a printer adapted to provide a document indicating the signals included in the message record and to provide a document indicating and/or including the CSA.

Referring now to Fig. 4, a flowchart of the software logic used in connection with the preferred embodiment is shown. Those skilled in the art could readily and easily write software implementing the flowchart shown in Fig. 4 using the instruction set, or other appropriate language associated with the particular microprocessor to be used. First block 400

5 passes to third block 404.

10

15

20

25

30

seventh block 414 program control passes to second block 402.

In sixth block 412, the computer 140 calculates the change in productivity and skill level.

5 From sixth block 412 program control passes to second decision block 416.

In second decision block 416, the computer 140 determines whether the productivity is deteriorating. If the productivity is not
10 deteriorating, program control passes back to second block 402. Otherwise, program control passes to eighth block 418.

In eighth block 418, the computer 140 provides productivity deterioration warning service
15 and agreement warning notice signals. From eighth block 418, program control returns to the main program.

The logic of Fig. 4 is performed frequently enough to provide the desired resolution and time
20 responsiveness for determining and alerting at least one of an operator, a service organization, the customer and an owner of the work machine 100 of a deterioration in productivity and preferably performed daily.

25 While aspects of the present invention have been particularly shown and described with reference to the preferred embodiment above, it will be understood by those skilled in the art that various additional embodiments may be contemplated without
30 departing from the spirit and scope of the present

09717573.112100

invention. For example, any of a number of different methods for determining the work or productivity of a work machine 100 could be readily and easily used to determine a CSA. Additionally, the expected
5 improvement in skill level data and relative skill levels may vary in any of many possible patterns and may not be normalized. However, a device or method incorporating such an embodiment should be understood to fall within scope of the present invention as
10 determined based on the claims below and any equivalence thereof.

Industrial Applicability

Work machines 100 having an attached
15 implement 120, such as motor graders, excavators, mining shovels, backhoe loaders, wheel loaders, track-type tractors, wheeled tractors, compactors, motor graders, and the like, are used for handling a payload, for example, moving earth. Typically, work
20 machines may be configured to perform various work cycles such as load and carry, truck loading, hard bank, clean up and the like.

Today, most customer support agreements are based on a level of machine maintenance or machine
25 availability. With the introduction of more intelligent machines 100 it is possible to measure the productivity during various work cycles and determine a CSA that guarantees certain productivity numbers.

These more intelligent machines 100 have many sensors and computers 140 that are used for information and control. This gives the machines 100 an ability to generate, track and store more information. Additionally, the inclusion of these devices in a machine 100 makes the machine 100 easier to operate and more productive. This is at least partially a result of automated aspects of various work cycles.

In general, sensors can be used to determine what the machine 100 is doing or the work cycle it is performing. The sensors can also determine the amount of payload that the machine 100 is handling. In the case of a wheel loader having a bucket as the implement 120, sensors can measure the amount of material in the bucket, the amount of fuel consumed to complete the task and the performance of the operator as compared against a predetermined performance level.

For example, it is known that an expert operator, in a truck loading operation, can load the bucket, back up turning, and go forward to dump the payload from the bucket into a truck and the tires only make three quarter ($3/4$) of a revolution. The sensors can monitor the number of tire revolutions performed by the operator performing the truck loading work cycle. The computer 140 is able to time the work cycle. Less skilled operators require many more revolutions and therefore, more time (e.g. inexperienced operators may perform the same work cycle using as many as two and one-half ($2 \frac{1}{2}$) tire

09717573.112100

revolutions and significantly more time). This information and productivity can be stored in a data storage device 145 along with average performance data for many work cycles.

5 In at least one embodiment of the present invention it is advantageous to provide an incentive to the operator for at least achieving a predetermined change in skill level. Such a predetermined change in skill level can be determined by considering the
10 normalized expected improvement in skill level data. Advantageously, the incentive is at least one of a reward, penalty, compensation and a failure to impose at least one of the reward, penalty and compensation and preferably includes a bonus provided to the
15 operator.

It is advantageous for the machine 100 to include a communications device 150 such as a wireless transmitter for transmitting information and productivity data to a distributed database where data
20 for numerous machines 100 can be stored. Preferably this information is transmitted at the end of each shift or day if multiple shifts are used.

Additionally, the change in skill level of the operator may be monitored and stored. The
25 relative skill level of an operator may be determined and stored for any given work cycle performed during a trial period near the time the machine is provided. As the operator gains experience, his/her skill level should increase and move up along the normalized
30 operator productivity curve. The expected progress of

the operator in this manner gives rise to the normalized expected improvement in skill level data.

5 In an embodiment of the present invention the machine 100 can be provided to a customer where it would be used for a period of time. At the end of the period, all of the information can be transmitted to a distributed computer 140 and analyzed. Based on this analysis a CSA can be selected or generated and provided. The productivity of the machine 100 can
10 continue to be monitored. If the computer 140 determines that the productivity is deteriorating, then a message record can be provided to the party guaranteeing the productivity of the machine 100 so that maintenance can be planned or conveniently
15 scheduled.

The apparatus and method of certain embodiments of the present invention, when compared with other methods and apparatus, may have the advantages of sensing the work performed by the
20 machine 100; calculating the productivity of the machine 100; selecting a CSA in response to the productivity; being used in a timely and efficient manner; and being more economical to manufacture and use. Such advantages are particularly worthy of
25 incorporating into the design, manufacture, and operation of work machines 100. In addition, the present invention may provide other advantages that have not been discovered yet.

It should be understood that while the
30 preferred embodiment as described in connection with a

0077573-112100

wheel loader, the present invention is readily adaptable to provide similar functions for other work machines 100. Other aspects, objects, and advantages of the present invention can be obtained from a study
5 of the drawings, the disclosure, and the appended claims.

09217573.112100

a computer adapted to
receive the sensor signal,
calculate the productivity of the
machine,

5 select and generate a guaranteed
productivity customer support agreement in
response to the productivity of the machine,
monitor the productivity of the
machine,

10 determine whether the productivity of
the machine is deteriorating, and
provide a productivity deterioration
warning notice signal in response to determining
the productivity of the machine is deteriorating.

15 4. The system of claim 3, wherein the
machine sensor includes at least one operation sensor
adapted to provide at least one operating sensor
signal indicative of the operation performed by the
20 machine, at least one payload sensor adapted to
provide at least one payload sensor signal indicative
of the payload handled by the machine and at least one
fuel sensor adapted to provide at least one fuel
consumption sensor signal indicative of the amount of
25 fuel consumed by the machine.

5. The system of claim 4, including at
least one data storage device adapted to store on a
storage medium information including empirical data,
30 values representing the sensor signals and normalized

009717573-112100

operator productivity data for at least one work cycle
and wherein the computer is adapted to compare the
sensor signals to the empirical data to determine a
work cycle performed by the machine, determine a skill
5 level of the operator and provide a skill level notice
signal, the skill level of the operator being
determined by comparing the productivity of the
machine with the normalized operator productivity data
for the work cycle and calculate the change in the
10 productivity of the machine and skill level of the
operator, the data storage device being adapted to
store the change in the productivity of the machine
and skill level of the operator.

6. A system for providing at least one
work machine controlled by at least one operator to a
customer, comprising:

at least one operation sensor adapted to
provide at least one operating sensor signal

indicative of the operation performed by the machine;

at least one payload sensor adapted to
provide at least one payload sensor signal indicative
of the payload handled by the machine;

at least one fuel sensor adapted to provide
25 at least one fuel consumption sensor signal indicative
of the amount of fuel consumed by the machine;

at least one data storage device adapted to
store on a storage medium information including
empirical data, values representing the sensor

30 signals, normalized operator productivity data for at

least one work cycle, normalized expected improvement
in skill level data for at least one work cycle and at
least one guaranteed productivity customer support
agreement having at least one minimum productivity

5 limit and corresponding price;

a computer including a CPU adapted to

receive the sensor signals,

compare the sensor signals to the
empirical data to determine a work cycle

10 performed by the machine,

calculate the productivity of the
machine and provide a productivity notice signal,
the productivity being a function of an amount of
fuel consumed and at least one of a payload

15 handled by the machine and an operation performed
by the machine,

determine a skill level of the operator
and provide a skill level notice signal, the
skill level of the operator being determined by
20 comparing the productivity of the machine with
the normalized operator productivity data for the
work cycle,

select and generate the guaranteed
productivity customer support agreement

25 establishing at least one minimum productivity
limit and corresponding price in response to the
skill level,

monitor the machine,

09717573.112100

continuously calculate the productivity of the machine and determine the skill level of the operator,

5 calculate the change in the productivity of the machine and skill level of the operator, the data storage device being adapted to store the change in the productivity of the machine and skill level of the operator,

10 determine whether the productivity of the machine is deteriorating as a function of at least one of the change in the productivity of the machine, the change in the skill level of the operator and the normalized expected improvement in skill level data,

15 provide a productivity deterioration warning notice signal in response to determining the productivity of the machine is deteriorating,

20 provide a service notice signal in response to the step of determining whether the productivity of the machine is deteriorating,

provide an agreement warning notice signal in response to the step of determining whether the productivity of the machine is deteriorating and considering the limit,

25 generate at least one message record, the message record including at least one of the signals and notice signals, and

the data storage device being adapted to store values representing the message record;
30 and

at least one communication device adapted to receive the message record and provide the message record to at least one of the operator, a service organization, the customer and an owner of the
5 machine.

7. A method of determining a guaranteed customer support agreement for a customer, the method comprising the steps of:
10 determining the productivity of the machine;
and
generating a guaranteed productivity customer support agreement establishing at least one minimum productivity limit.
15

8. The method of claim 7, wherein an operator operates the machine and including the step of determining a skill level of the operator.

9. The method of claim 8, including the steps of determining whether the productivity of the machine is deteriorating and communicating a productivity deterioration warning notice to at least one of the operator, a service organization, the
20 customer and an owner of the machine.
25

10. A method of providing at least one work machine to a customer, the method comprising the steps of:

determining the productivity of the machine,
the productivity being at least a function of a time
period, a fuel consumed and at least one of a payload
handled by the machine and an operation performed by
5 the machine;

determining a skill level of the operator;
generating a guaranteed productivity
customer support agreement establishing at least one
minimum productivity limit and corresponding price in
10 response to the skill level;

determining whether the productivity of the
machine is deteriorating; and

communicating a productivity deterioration
warning notice to at least one of the operator, a
15 service organization, the customer and an owner of the
machine.

11. The method of claim 10, including the
steps of monitoring the operation of the machine and
20 determining a work cycle performed by the machine.

12. The method of claim 11, wherein the
machine is operated by an operator and including the
steps of comparing the productivity of the machine
25 with normalized operator productivity data for the
work cycle and determining a skill level of the
operator in response to the step of comparing the
productivity of the machine with the productivity
data.

13. The method of claim 12, including the steps of performing comparisons of the productivity of the machine with the productivity data and determining the change in the skill level of the operator in response to the step of performing subsequent comparisons of the productivity of the machine with the productivity data.

14. The method of claim 13, including the step of providing an incentive to the operator for at least achieving a predetermined change in skill level, such predetermined change in skill level being determined by considering a normalized expected improvement in skill level, and the incentive being at least one of a reward, penalty, compensation, and failure to impose at least one of a reward, penalty and compensation.

15. The method of claim 13, including the steps of determining a productivity deterioration warning notice in response to performing subsequent comparisons of the productivity of the machine with the productivity data and considering the normalized expected improvement in skill level, determining a service notice in response to the step of determining whether the productivity of the machine is deteriorating and determining an agreement warning in response to the step of determining whether the productivity of the machine is deteriorating and considering the limit.

16. The method of claim 15, including the step of generating at least one message record and including in the message record a signal indicative of at least one of the productivity, skill level, service notice, agreement warning, productivity deterioration warning notice, time period, fuel consumed, payload handled by the machine and the operation performed by the work machine.

10

17. A method of providing at least one work machine controlled by at least one operator to a customer, the method comprising the steps of:

monitoring the operation of the machine;
15 determining a work cycle performed by the machine;

determining the productivity of the machine, the productivity being at least a function of a time period, a fuel consumed and at least one of a payload handled by the machine and an operation performed by the machine;

20

comparing the productivity of the machine with normalized operator productivity data for the work cycle;

25

determining a skill level of the operator in response to the step of comparing the productivity of the machine with the productivity data;

generating a guaranteed productivity customer support agreement establishing at least one

05717573-112100

minimum productivity limit and corresponding price in response to the skill level;

monitoring the machine;

performing subsequent comparisons of the
5 productivity of the machine with the productivity data;

determining the change in the skill level of the operator in response to the step of performing subsequent comparisons of the productivity of the
10 machine with the productivity data;

providing an incentive to the operator for at least achieving a predetermined change in skill level, such predetermined change in skill level being determined by considering a normalized expected
15 improvement in skill level, and the incentive being at least one of a reward, penalty, compensation, and failure to impose at least one of a reward, penalty and compensation;

determining whether the productivity of the
20 machine is deteriorating and determining a productivity deterioration warning notice in response to performing subsequent comparisons of the productivity of the machine with the productivity data and considering the normalized expected improvement in
25 skill level;

determining a service notice in response to the step of determining whether the productivity of the machine is deteriorating;

determining an agreement warning in response
30 to the step of determining whether the productivity of

09747573-112100

the machine is deteriorating and considering the limit;

generating at least one message record;

including in the message record a signal

5 indicative of at least one of the productivity, skill level, service notice, agreement warning, productivity deterioration warning notice, time period, fuel consumed, payload handled by the machine and the operation performed by the work machine; and

10 communicating the message record to at least one of the operator, a service organization, the customer and an owner of the machine.

18. A work machine adapted to be controlled
15 by an operator and for acting upon a load through a plurality of work cycles, comprising:

a frame;

a plurality of ground engaging devices supporting the frame;

20 an operator compartment supported by the ground engaging devices;

an implement having a linkage for operably connecting the implement to the frame;

25 an engine operably coupled to the ground engaging devices; and

a system for determining a guaranteed productivity support agreement for a customer, including:

at least one machine sensor adapted to
provide at least one machine sensor signal indicative
of the work performed by the machine;

at least one computer adapted to
5 receive the sensor signal,
calculate the productivity of the
machine, and
select a guaranteed productivity
customer support agreement in response to the
10 productivity.

19. The work machine of claim 18, wherein
the computer is adapted to determine whether the
productivity of the machine is deteriorating and
15 provide a productivity deterioration warning notice
signal in response to determining the productivity of
the machine is deteriorating.

20. A work machine adapted to be controlled
20 by an operator and for acting upon a load through a
plurality of work cycles, comprising:
a frame;
a plurality of ground engaging devices
supporting the frame;
25 an operator compartment supported by the
ground engaging devices;
an implement having a linkage for operably
connecting the implement to the frame;
an engine operably coupled to the ground
30 engaging devices; and

0974573-113100

a system for measuring operator productivity of at least one work machine for a customer, including:

at least one machine sensor adapted to
5 provide at least one machine sensor signal indicative of the operation performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine;
at least one data storage device
10 adapted to store information on a storage medium;
a computer adapted to
receive the sensor signals,
calculate the productivity of the
machine, the productivity being a function
15 of an amount of fuel consumed and at least one of a payload handled by the machine and an operation performed by the machine,
calculate the change in the
productivity of the machine, the data
20 storage device being adapted to store the change in the productivity of the machine;
and
determine whether the productivity of
the machine is deteriorating.

25

21. A system for measuring operator productivity of at least one work machine for a customer, comprising:

at least one machine sensor adapted to
30 provide at least one machine sensor signal indicative

05717573-112100

of the operation performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine; and

5 a computer including a CPU adapted to
receive the sensor signals and
calculate the productivity of the
machine, the productivity being a function of an
amount of fuel consumed and at least one of a
payload handled by the machine and an operation
10 performed by the machine.

22. The system of claim 21, wherein the
computer is adapted to calculate the change in the
productivity of the machine.

15 23. A system for measuring operator
productivity of at least one work machine for a
customer, comprising:

20 at least one machine sensor adapted to
provide at least one machine sensor signal indicative
of the operation performed by the machine, the payload
handled by the machine and the amount of fuel consumed
by the machine;

25 at least one data storage device adapted to
store information on a storage medium;

a computer adapted to
receive the sensor signals,
calculate the productivity of the
machine, the productivity being a function of an
30 amount of fuel consumed and at least one of a

09747573-112100

payload handled by the machine and an operation performed by the machine,

calculate the change in the productivity of the machine, the data storage device being adapted to store the change in the productivity of the machine; and

determine whether the productivity of the machine is deteriorating.

24. The system of claim 23, wherein the machine sensor includes at least one operation sensor adapted to provide at least one operating sensor signal indicative of the operation performed by the machine, at least one payload sensor adapted to provide at least one payload sensor signal indicative of the payload handled by the machine and at least one fuel sensor adapted to provide at least one fuel consumption sensor signal indicative of the amount of fuel consumed by the machine.

25. The system of claim 24, wherein the information includes empirical data, values representing the sensor signals, normalized operator productivity data for at least one work cycle and the computer is adapted to compare the sensor signals to the empirical data to determine a work cycle performed by the machine, determine a skill level of the operator and provide a skill level notice signal, the skill level of the operator being determined by comparing the productivity of the machine with the

normalized operator productivity data for the work cycle, calculate the change in the skill level of the operator and determine whether the productivity of the machine is deteriorating as a function of at least one
5 of the change in the productivity of the machine, the change in the skill level of the operator and the normalized expected improvement in skill level.

26. The system of claim 25, wherein the
10 computer is adapted to provide a productivity deterioration warning notice signal in response to determining the productivity of the machine is deteriorating and generate at least one message record including the notice signal, the data storage device
15 is adapted to store values representing the message record and at least one communication device is adapted to receive the message record and provide the message record to at least one of the operator, a service organization, the customer and an owner of the
20 machine.

27. A method of providing incentives to an operator of a work machine, the method comprising the steps of:
25 determining a work cycle performed by the machine;
determining the productivity of the machine;
comparing the productivity of the machine
with normalized operator productivity data for the
30 work cycle;

determining the change in the skill level of
5 the operator in response to comparing the productivity
of the machine with the productivity data; and
providing an incentive to the operator for
at least achieving a predetermined change in skill
level.

28. The method of claim 27, including the steps of generating at least one message record including a signal indicative of the skill level and communicating the message record to at least one of the operator, a service organization, a customer and an owner of the machine

determining a work cycle performed by the machine;

determining the productivity of the machine, the productivity being at least a function of a time 25 period, a fuel consumed and at least one of a payload handled by the machine and an operation performed by the machine;

```

        comparing the productivity of the machine
    with normalized operator productivity data for the
30  work cycle;

```

determining a skill level of the operator in response to the step of comparing the productivity of the machine with the productivity data;

5 determining the change in the skill level of the operator in response to comparing the productivity of the machine with the productivity data;

10 providing an incentive to the operator for at least achieving a predetermined change in skill level, such predetermined change in skill level being determined by considering a normalized expected improvement in skill level, and the incentive being at least one of a reward, penalty, compensation, and failure to impose at least one of a reward, penalty and compensation;

15 determining whether the productivity of the machine is deteriorating and determining a productivity deterioration warning notice in response to performing subsequent comparisons of the productivity of the machine with the productivity data and considering the normalized expected improvement in skill level;

20 generating at least one message record including a signal indicative of the skill level; and communicating the message record to at least 25 one of the operator, a service organization, a customer and an owner of the machine.

30. A system for determining when a work machine needs service, comprising:

at least one machine sensor adapted to provide at least one machine sensor signal indicative of the operation performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine; and

a computer adapted to receive the sensor signals, calculate the productivity of the machine, determine a skill level of the operator, calculate the change in the productivity of the machine and skill level of the operator, determine whether the productivity of the machine is deteriorating and provide a service notice signal in response to the step of determining whether the productivity of the machine is deteriorating.

31. The system of claim 30, wherein whether the productivity of the machine is deteriorating is determined as a function of at least one of the change in the productivity of the machine, the change in the skill level of the operator and the normalized expected improvement in skill level data.

32. The system of claim 30, wherein the computer is adapted to generate at least one message record, the message record including the service notice signal and including at least one communication device adapted to receive the message record and provide the message record to at least one of the operator, a service organization, the customer and an owner of the machine.

33. A system for determining when a work machine needs service, comprising:

at least one machine sensor adapted to
5 provide at least one machine sensor signal indicative of the operation performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine; and

at least one data storage device adapted to
10 store on a storage medium information including normalized operator productivity data for at least one work cycle and normalized expected improvement in skill level data;

a computer adapted to
15 receive the sensor signals,
calculate the productivity of the machine,
determine a skill level of the operator, the skill level of the operator being
20 determined by comparing the productivity of the machine with the normalized operator productivity data for the work cycle,

calculate the change in the
productivity of the machine and skill level of
25 the operator,

determine whether the productivity of the machine is deteriorating as a function of at least one of the change in the productivity of the machine, the change in the skill level of the

002157341200

operator and the normalized expected improvement
in skill level data,

provide a service notice signal in
response to the step of determining whether the
5 productivity of the machine is deteriorating,
generate at least one message record,
the message record including the
service notice signal; and
at least one communication device adapted to
10 receive the message record and provide the message
record to at least one of the operator, a service
organization, the customer and an owner of the
machine.

34. The system of claim 33, wherein the
15 productivity is a function of an amount of fuel
consumed and at least one of a payload handled by the
machine and an operation performed by the machine.

35. A work machine adapted to be controlled
20 by an operator and for acting upon a load through a
plurality of work cycles, comprising:
a frame;
a plurality of ground engaging devices
25 supporting the frame;
an operator compartment supported by the
ground engaging devices;
an implement having a linkage for operably
connecting the implement to the frame;

0971573-11200

an engine operably coupled to the ground
engaging devices; and

a system for determining fees to be paid by
a customer that are based on machine productivity,
5 including:

at least one machine sensor adapted to
provide at least one machine sensor signal indicative
of the operation performed by the machine, the payload
handled by the machine and the amount of fuel consumed
10 by the machine; and

a computer adapted to receive the sensor
signals, calculate the productivity of the machine,
determine a skill level of an operator of the machine,
the skill level of the operator being determined by
15 comparing the productivity of the machine with the
normalized operator productivity data for the work
cycle, and select an agreement establishing a price in
response to the skill level.

20 36. The work machine of claim 35, wherein
the productivity is a function of an amount of fuel
consumed and at least one of a payload handled by the
machine and an operation performed by the machine.

25 37. The work machine of claim 35, wherein
the agreement establishes at least one minimum
productivity limit and corresponding price.

30 38. The work machine of claim 35, including
at least one communication device adapted to receive

the price and provide the price to at least one of the operator, a service organization, the customer and an owner of the machine.

- 5 39. A work machine adapted to be controlled by an operator and for acting upon a load through a plurality of work cycles, comprising:
- a frame;
 - a plurality of ground engaging devices
 - 10 supporting the frame;
 - an operator compartment supported by the ground engaging devices;
 - an implement having a linkage for operably connecting the implement to the frame;
 - 15 an engine operably coupled to the ground engaging devices; and
 - a system for determining when a work machine needs service, including:
 - at least one machine sensor adapted to
 - 20 provide at least one machine sensor signal indicative of the operation performed by the machine, the payload handled by the machine and the amount of fuel consumed by the machine; and
 - a computer adapted to receive the sensor
 - 25 signals, calculate the productivity of the machine, determine a skill level of the operator, calculate the change in the productivity of the machine and skill level of the operator, determine whether the productivity of the machine is deteriorating and
 - 30 provide a service notice signal in response to the

step of determining whether the productivity of the machine is deteriorating.

40. The work machine of claim 39, wherein
5 whether the productivity of the machine is
deteriorating is determined as a function of at least
one of the change in the productivity of the machine,
the change in the skill level of the operator and the
normalized expected improvement in skill level data.

10

41. The work machine of claim 39, wherein
the computer is adapted to generate at least one
message record, the message record including the
service notice signal and including at least one
15 communication device adapted to receive the message
record and provide the message record to at least one
of the operator, a service organization, the customer
and an owner of the machine.

20

42. A system for determining fees to be
paid by a customer that are based on machine
productivity, comprising:

at least one machine sensor adapted to
provide at least one machine sensor signal indicative
25 of the operation performed by the machine, the payload
handled by the machine and the amount of fuel consumed
by the machine; and

a computer adapted to receive the sensor
signals, calculate the productivity of the machine,
30 determine a skill level of an operator of the machine,

the skill level of the operator being determined by comparing the productivity of the machine with the normalized operator productivity data for the work cycle, and select an agreement establishing a price in response to the skill level.

43. The system of claim 42, wherein the productivity is a function of an amount of fuel consumed and at least one of a payload handled by the machine and an operation performed by the machine.

44. The system of claim 42, wherein the agreement establishes at least one minimum productivity limit and corresponding price.

45. The system of claim 42, including at least one communication device adapted to receive the price and provide the price to at least one of the operator, a service organization, the customer and an owner of the machine.

09717573-112100

Abstract of the Disclosure

APPARATUS AND METHOD OF PROVIDING A WORK MACHINE

5 An apparatus and method of providing a work
machine to a customer is disclosed. An embodiment
includes at least one machine sensor and at least one
computer. Signals indicative of the work performed by
the machine are provided. The computer receives the
10 signals and calculates the productivity of the
machine.

09717573-1.12100

Fig. 1 -




Fig-2

UNIT 11: 22/11/2020




FIG. 3





Fig - 4 -

4/4



09217573-112100

DECLARATION AND POWER OF ATTORNEY

I, Thomas P. Muller, declare that I am a citizen of the United States of America, residing at Montgomery, Illinois, and that I believe I am the original, first, and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

APPARATUS AND METHOD OF PROVIDING A WORK MACHINE

the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims.

I hereby claim the benefit under Title 35, United States Code, §119(c) of any United States provisional application(s) listed below:

Provisional Application Serial Number: 60/210,058

I acknowledge the duty to disclose to the Patent and Trademark Office all information known to be material to patentability as defined in §1.56. I further declare that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns.

I hereby appoint Byron G. Buck II, Patent Office Reg. No. 40,537, telephone (309) 675-6717, Joseph W. Keen, Patent Office Reg. No. 28,432, telephone (309) 675-5753, Robert J. Hampsch, Patent Office Reg. No. 36,155, telephone (309) 675-5214, and R. Carl Wilbur, Patent Office Reg. No. 36,056, telephone (309) 675-5847, my attorneys and/or agents, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected with this application. Please address all correspondence to: Byron G. Buck II, Caterpillar Inc., Intellectual Property Department, AB6490, 100 N.E. Adams Street, Peoria, Illinois 61629-6490.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

THOMAS P. MULLER

Date

Post Office Address:

26 Caymen Drive

Montgomery, Illinois 60538

09717573-112100